



# LC1213

## 250mA Low Consumption Linear Regulator

### DESCRIPTION

LC1213 series is a group of positive voltage output, low power consumption, low dropout voltage, three terminal regulator. It can provide 200mA output current when input / output voltage differential drops to 418mV ( $V_{out}=3.3V$ ), And it also provides foldback short-circuit protection and output current limit function. The very low power consumption of LC1213 ( $I_q=3\mu A$ ) can greatly improve natural life of batteries.

LC1213 can provide output value in the range of 1.2V~5.0V in 0.1V steps. It also can customized on command.

LC1213 includes high accuracy voltage reference, error amplifier, current limit circuit and output driver module.

LC1213 has well load transient response and good temperature characteristic, And it uses trimming technique to guarantee output voltage accuracy within  $\pm 2\%$ .


### FEATURES

- Low Power Consumption: 3 $\mu A$ (Typ.)
- Maximum Output Current: 250mA
- Small Dropout Voltage  
211mV@100mA ( $V_{out}=3.3V$ )  
418mV@200mA ( $V_{out}=3.3V$ )
- Input Voltage Range: 2.5V~16V
- Output Voltage Range: 1.2V~5.0V (customized on command in 0.1V steps)
- Highly Accurate:  $\pm 2\%$ ( $\pm 1\%$  customized)
- Output Current Limit: 500mA
- Foldback Short-circuit Current: 85mA

### APPLICATIONS

- Battery Powered equipment
- Power Management of MP3、PDA、DSC、Mouse、PS2 Games
- Reference Voltage Source Regulation after Switching Power


### TYPICAL APPLICATION



**NOTE:** Input capacitor ( $C_{in}=1\mu F$ ) and Output capacitor ( $C_{out}=1\mu F$ ) are recommended in all application circuit. Ceramic capacitor is recommended.

### ELECTRICAL CHARACTERISTICS

#### Load Regulation



## ORDERING INFORMATION

LC1213 ①②③④⑤

Code	Description
①	Temperature&Rohs: C:-40~85°C ,Pb Free Rohs Std.
②	Package type: B3:SOT-23-3 B3B:SOT-23-3(B) C3:SOT-89-3 C3B:SOT-89-3(B)
③	Packing type: TR:Tape&Reel (Standard)
④	Output voltage: e.g. 12=1.2V 15=1.5V 50=5.0V
⑤	Voltage accuracy: 1=±1% Blank(default)=±2%

## ABSOLUTE MAXIMUM RATING

Parameter	Value	
Max Input Voltage	20V	
Operating Junction Temperature(Tj)	125°C	
Ambient Temperature(Ta)	-40°C -85°C	
Power Dissipation	SOT-23-3	250mW
	SOT-89-3	500mW
Storage Temperature(Ts)	-40°C -150°C	
Lead Temperature & Time	260°C,10S	

### Note:

Exceed these limits to damage to the device.  
Exposure to absolute maximum rating conditions may affect device reliability.

## RECOMMENDED WORK CONDITIONS

Item	Min	Recom- mended	Max.	Unit
Input Voltage Range			16	V
Ambient Temperature	-40		85	°C

## PIN CONFIGURATION

<b>Product Classification</b>		LC1213CB3TR□□□
<b>Marking</b>		SOT-23-3
DXYW	D:Product Code	
	X:Output Voltage	
	YW: Date Code	
<b>Product Classification</b>		LC1213CB3BTR□□□
<b>Marking</b>		SOT-23-3 (B)
DXYWI	D:Product Code	
	X:Output Voltage	
	YW: Date Code	
<b>Product Classification</b>		LC1213CC3TR□□□
<b>Marking</b>		SOT-89-3
AAXX LLBYW	AA:Product Code	
	XX: Output Voltage	
	LL: LOT NO.	
	B:FAB Code	
	YW: Date Code	
<b>Product Classification</b>		LC1213CC3BTR□□□
<b>Marking</b>		SOT-89-3 (B)
AAXXI LLBYW	AA:Product Code	
	XX: Output Voltage	
	LL: LOT NO.	
	B:FAB Code	
	YW: Date Code	


Y: The Year of manufacturing, "1" stands for year 2011, "2" stands for year 2012, and "8" stands for year 2018.  
W: The week of manufacturing. "A" stands for week 1, "Z" stands for week 26, "A" stands for week 27, "Z" stands for week 52.

## ELECTRICAL CHARACTERISTICS

(Test Conditions:  $C_{in}=1\mu F$ ,  $C_{out}=1\mu F$ ,  $T_A=25^\circ C$ , Unless Otherwise Specified)

Symbol	Parameter	Conditions	Min	Type	Max	Units
$V_{in}$	Input Voltage				16	V
$V_{out}$	Output Voltage		$V_{out} \times 0.98$		$V_{out} \times 1.02$	V
$I_{out(Max.)}$	Maximum Output Current	$V_{in}-V_{out}=1V$	250			mA
Dropout Voltage	Input-Output Voltage Differential	$I_{out}=100mA$ $V_{out} = 3.3V$		210	400	mV
$\frac{\Delta V_{out}}{\Delta V_{in} \cdot V_{out}}$	Line Regulation	$I_{out}=10mA$ $2V \leq V_{in} \leq 16V$		0.2	0.3	%/V
$\Delta V_{out}$	Load Regulation	$V_{in} = \text{Set } V_{out} + 1V$ $1mA \leq I_{out} \leq 100mA$		20	40	mV
$I_q$	Quiescent Current	$V_{in} = \text{Set } V_{out} + 1V$		3	5	$\mu A$
$\frac{\Delta V_{out}}{\Delta T \cdot V_{out}}$	Output Voltage Temperature Coefficient	$I_{out}=10mA$		100		ppm/ $^\circ C$

## BLOCK DIAGRAM



## EXPLANATION


LC1213 is a series of low dropout voltage and low power consumption three pins regulator. Its application circuit is very simple, which only needs two outside capacitors. It is composed of these modules: high accuracy voltage reference, current limit circuit, error amplifier, output driver and power transistor.

Current Limit module can keep chip and power system away from danger when load current is more than 500mA.


LC1213 uses trimming technique to assure the accuracy of output value within  $\pm 2\%$ , at the same time, temperature compensation is elaborately considered in this chip, which makes LC1213's temperature coefficient within 100ppm/ $^\circ C$ .

## TYPICAL PERFORMANCE CHARACTERISTICS


### Load Regulation




### Line Regulation




### Dropout



### Iq




### Current Limit




## Line transient response

Vin=11V~12V, Ch1—Vin, Ch2—Vout



## Load transient response

Iout=1mA~100mA, Ch2—Vout, Ch4—Iout



## PACKAGE LINE

Package	SOT-23-3	Devices per reel	3000Pcs	Unit	mm
Package dimension:					
<p>Technical drawing of the SOT-23-3 package. The top view shows a width of <math>2.9 \pm 0.2</math> mm and a lead pitch of <math>1.9 \pm 0.2</math> mm. The lead width is <math>0.4 \pm 0.1</math> mm. The lead height is <math>1.6 \pm 0.2</math> mm. The total height is <math>2.8 \pm 0.3</math> mm. The lead length is <math>0.95</math> mm. The side view shows a maximum width of <math>1.4</math> mm, a lead height of <math>1.1</math> mm (tolerance <math>+0.2/-0.1</math>), a lead length of <math>0.8</math> mm, and a lead thickness of <math>0.16</math> mm (tolerance <math>+0.1/-0.06</math>). The lead angle is <math>0.2</math> mm minimum. The perspective view shows the package from a different angle.</p>					

Package	SOT-89-3	Devices per reel	1000Pcs	Unit	mm
Package Dimension:					
<p>Technical drawing of the SOT-89-3 package. The top view shows a width of <math>4.5 \pm 0.1</math> mm and a lead pitch of <math>1.5 \pm 0.1</math> mm. The lead width is <math>0.4 \pm 0.1</math> mm. The lead height is <math>0.4</math> mm. The total height is <math>4.25</math> mm maximum. The lead length is <math>2.5 \pm 0.1</math> mm. The lead angle is <math>0.8</math> mm minimum. The side view shows a maximum width of <math>1.5 \pm 0.1</math> mm, a lead height of <math>0.4 \pm 0.1</math> mm, and a lead length of <math>0.4 \pm 0.1</math> mm. The perspective view shows the package from a different angle.</p>					